MULE PRO-MX™ SE







POWER

Engine 4-stroke, single cylinder, SOHC, 4-valve liquid-cooled

695cc Displacement

Maximum Torque 42.7 lb-ft @ 5,000 rpm

Bore x Stroke 102.0 x 85.0 mm

Compression Ratio 10.3:1

Fuel System DFI® with 44mm throttle body

Transmission Continuously Variable Transmission (CVT) with centrifugal

clutch, (H,L,N,R)

Final Drive Selectable 2WD/4WD, shaft, Dual mode rear differential

with differential lock

Engine Braking Yes

Alternator Output

(max)

35.7 amp

CAPABILITY

Double wishbone/8.6 in Front Suspension /

Wheel Travel

Rear Suspension / **Wheel Travel**

Double wishbone/9.1 in

Front Tires

25x10.00-12, radial 25x10.00-12, radial

Rear Tires Steering

Electric Power Steering (EPS), Tilt steering

Park Brake Type

Independent, Mechanical Disc

Front Brakes

Dual Disc, 2 piston caliper

Rear Brakes

Dual Disc, 1 piston caliper

Ground Clearance 10.6 in

Fuel Capacity 9.5 gal

Turning Radius 14.0 ft

Cargo Bed

Dimensions (LxWxH)

Cargo Bed Load 699 lb / 600 lb CA Model

Capacity

Payload Capacity 1,200 lb

Seating Capacity

Towing Capacity 1,500 lb

(2) Halogen headlights. (2) LED headlights Lighting

33.4 x 44.1 x 9.1 in

DETAILS

Overall Length 111.4 in

Overall Width 60.0 in

Overall Height 75.8 in

Curb Weight 1,622.9 lb*

Wheelbase 78.9 in

Instruments Multi-function display includes digital speedometer, fuel

gauge, odometer, hour meter, clock, dual trip meters, 2WD/4WD indicator, water temperature warning indicator, EPS warning indicators, neutral, reverse and parking indicators, differential indicator lamp, seatbelt reminder

lamps

Wheel Type Alloy

Additional Features

Roof, Winch, Cast Aluminum Wheels, Painted Body Panels

Color Choices Galaxy Silver

Kawasaki STRONG 3-Year Limited Warranty Warrantv

Scan with camera to view videos, key features and more.

