## **BRUTE FORCE® 750 EPS**







D	N	١	M	Г	D
г	u	١	N	E	π

Engine 4-stroke, V-twin, SOHC, liquid-cooled

Displacement 749c

Bore x Stroke 85.0 x 66.0mm

Compression Ratio 9.3:1

Maximum Torque 42.7 lb-ft @ 4750 rpm

Fuel System DFI® with two 36mm throttle bodies

Ignition Digital DC-CDI

Transmission Automatic CVT (H,L,N,R)

Final Drive Selectable 2WD/4WD with variable control front differential

lock, shaft

## **CAPABILITY**

Front Suspension / Double wishbone, adjustable spring preload/6.9 in Wheel Travel

Rear Suspension / Wheel Travel

Double wishbone, adjustable spring preload/7.4 in

Front Tires

AT 25 x 8-12

Rear Tires AT 25 x 10-12

Front Brakes Dual hydraulic 176mm discs with 2-piston calipers

Rear Brakes Sealed, oil-bathed, multi-disc with independent park brake

**Ground Clearance** 9.0 in/9.6 in (max preload)

Starting System Electric

Fuel Capacity 5.0 gal

Steering Rack-and-pinion w/ Electric Power Steering (EPS)

Electronic Power Yes

Steering (EPS)

Turning Radius 10.5 ft

Towing Capacity 1,250 lb

Total Rack Capacity 264.5 lb

Rack Capacity, Front/

Rear

**Lighting** All-LED lighting

## **DETAILS**

Frame Type Double-cradle, high-tensile tubular steel

88.0/176.0 lb

Tread Width 37.0/35.6 in

Overall Length 86.0 in

Overall Width 46.1 in

Overall Height 47.6 in

Seat Height 35.2 in

Curb Weight 732.1 lb\*

Wheelbase 50.6 in

**Instruments** Digital speedometer, 2WD/4WD drive indicator, fuel gauge,

odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and

battery voltage)

**Special Features** Full-color TFT Instrumentation, KQR™ system

Color Choices Grayish Blue

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.

