2024 **BRUTE FORCE® 750 LE EPS CAMO**





TRUETIMBER® STRATA



Rack-and-pinion w/ Electric Power Steering (EPS)

POWER

		El
Engine	4-stroke, V-twin, SOHC, liquid-cooled	St
Displacement	749cc	Tu
Bore x Stroke	85.0 x 66.0mm	Тс
Compression Ratio	9.3:1	Тс
Maximum Torque	42.7 lb-ft @ 4750 rpm	Ra Re
Fuel System	DFI® with two 36mm throttle bodies	Lis
Ignition	Digital DC-CDI	LI
Transmission	Automatic CVT (H,L,N,R)	D
Final Drive	Selectable 2WD/4WD with variable control front differential lock, shaft	Fr

CAPABILITY

Front Suspension / Wheel Travel	Double wishbone, adjustable spring preload/6.9 in	
Rear Suspension / Wheel Travel	Double wishbone, adjustable spring preload/7.4 in	
Front Tires	AT 25 x 8-12	
Rear Tires	AT 25 x 10-12	
Front Brakes	Dual hydraulic 176mm discs with 2-piston calipers	
Rear Brakes	Sealed, oil-bathed, multi-disc with independent park brake	
Ground Clearance	9.0 in/9.6 in (max preload)	
Starting System	Electric	
Fuel Capacity	5.0 gal	

Electronic Power Steering (EPS)YesTurning Radius10.5 ftTowing Capacity1,250 lbTotal Rack Capacity264.5 lbRack Capacity, Front/ Rear88.0/176.0 lbLightingAll-LED lighting	-	
Towing Capacity1,250 lbTotal Rack Capacity264.5 lbRack Capacity, Front/ Rear88.0/176.0 lb		Yes
Total Rack Capacity 264.5 lb Rack Capacity, Front/ Rear 88.0/176.0 lb	Turning Radius	10.5 ft
Rack Capacity, Front/ 88.0/176.0 lb Rear	Towing Capacity	1,250 lb
Rear	Total Rack Capacity	264.5 lb
Lighting All-LED lighting	1 27 -	88.0/176.0 lb
	Lighting	All-LED lighting

DETAILS

Steering

	Frame Type	Double-cradle, high-tensile tubular steel
l	Tread Width	37.0/35.6 in
	Overall Length	86.0 in
	Overall Width	46.1 in
	Overall Height	47.6 in
	Seat Height	35.2 in
	Curb Weight	732.1 lb*
	Wheelbase	50.6 in
odoı (12h, char light		Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and battery voltage)
	Special Features	Full-color TFT Instrumentation, KQR™ system
	Color Choices	TRUETIMBER® STRATA
	Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit costa-rica.kawasaki-la.com for full product details.