

2024

# KLX®150

**Kawasaki**  
Let the Good Times Roll®



LIME GREEN



## POWER

<b>Engine</b>	4st, 1-cyl, SOHC, A/C
<b>Displacement</b>	144cc
<b>Bore x Stroke</b>	58.0 x 54.4 mm
<b>Compression Ratio</b>	9.5:1
<b>Fuel System</b>	Carburettor: NCV24
<b>Ignition</b>	DC-CDI
<b>Transmission</b>	5-speed, return shift, with wet multi-disc manual clutch
<b>Final Drive</b>	Chain

## PERFORMANCE

<b>Front Suspension / Wheel Travel</b>	Horquilla telescópica/185 mm
<b>Rear Suspension / Wheel Travel</b>	Uni-Trak® swingarm/192 mm
<b>Front Tire</b>	2.75-21 45P

<b>Rear Tire</b>	4.10-18 59P
<b>Front Brakes</b>	Single disc
<b>Rear Brakes</b>	Single disc

## DETAILS

<b>Frame Type</b>	Perimeter, steel
<b>Rake/Trail</b>	26.9° /110 mm
<b>Overall Length</b>	2,050 mm
<b>Overall Width</b>	830 mm
<b>Overall Height</b>	1,155 mm
<b>Ground Clearance</b>	300 mm
<b>Seat Height</b>	865 mm
<b>Curb Weight</b>	118 kg
<b>Fuel Capacity</b>	6.9 L
<b>Wheelbase</b>	1,345 mm
<b>Color Choices</b>	Lime Green

Scan with camera  
to view videos,  
key features  
and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit costa-rica.kawasaki-la.com for full product details.