


2024

KLX[®]300SM

Kawasaki
Let the Good Times Roll[®]



POWER

| | |
|-------------------|---|
| Engine | 4-stroke single, DOHC, liquid-cooled |
| Displacement | 292cc |
| Bore x Stroke | 78.0 x 61.2mm |
| Compression Ratio | 11.1:1 |
| Fuel System | DFI [®] with 34mm Keihin throttle body |
| Ignition | CDI |
| Transmission | 6-speed, return shift with wet multi-disc manual clutch |
| Final Drive | Chain |

PERFORMANCE

| | |
|---------------------------------|---|
| Front Suspension / Wheel Travel | 43mm inverted cartridge fork with adjustable compression damping / 9.1 in |
| Rear Suspension / Wheel Travel | Uni-Trak [®] gas charged shock with piggyback reservoir with adjustable rebound damping and spring preload/ 8.1 in |
| Front Tire | 110/70-17 |

| | |
|--------------|--|
| Rear Tire | 130/70-17 |
| Front Brakes | Single 300mm petal disc with a dual-piston caliper |
| Rear Brakes | Single 240mm petal disc with single-piston caliper |

DETAILS

| | |
|------------------|---------------------------|
| Frame Type | Semi Double Cradle |
| Rake/Trail | 25.0° / 2.8 in |
| Overall Length | 83.3 in |
| Overall Width | 31.1 in |
| Overall Height | 44.7 in |
| Ground Clearance | 9.3 in |
| Seat Height | 33.9 in |
| Curb Weight | 304.3 lb* |
| Fuel Capacity | 2.0 gal |
| Wheelbase | 56.5 in |
| Color Choices | Battle Gray, Phantom Blue |
| Warranty | 12 Month Limited Warranty |

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2026 Kawasaki Motors Corp., U.S.A. Specifications subject to change. Visit costa-rica.kawasaki-la.com for full product details.