

2024

NINJA[®] ZX[™]-10R

Kawasaki

Let the Good Times Roll[®]



 METALLIC FLAT SPARK BLACK/EBONY



POWER		Front Tire	120/70 ZR17
Engine	4-stroke, In-Line Four, DOHC, 16-valve, liquid-cooled	Rear Tire	190/55 ZR17
Displacement	998cc	Front Brakes	Brembo dual semi-floating 330mm discs with dual radial mounted monobloc 4-piston calipers, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)
Bore x Stroke	76.0 x 55.0mm	Rear Brakes	Single 220mm disc with aluminum single-piston caliper, Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only)
Compression Ratio	13.0:1	DETAILS	
Fuel System	DFI [®] with 47mm throttle bodies	Frame Type	Aluminum perimeter
Ignition	TCBI with Digital Advance	Rake/Trail	25.0° / 4.1 in
Transmission	6-speed, return shift	Overall Length	82.1 in
Final Drive	Sealed chain	Overall Width	29.5 in
Electronic Rider Aids	Öhlins Electronic Steering Damper, Electronic Cruise Control, Power Modes, Kawasaki Launch Control Mode (KLCM), Kawasaki Intelligent anti-lock Brake System (KIBS) (ABS only), Sport-Kawasaki TRaction Control (S-KTRC), Kawasaki Engine Braking Control, Kawasaki Quick Shifter (KQS) (upshift & downshift), Kawasaki Corner Management Function (KCMF)	Overall Height	46.7 in
PERFORMANCE		Ground Clearance	5.3 in
Front Suspension / Wheel Travel	43mm inverted Balance Free Fork, adjustable stepless rebound and compression damping, spring preload adjustability/4.7 in	Seat Height	32.9 in
Rear Suspension / Wheel Travel	Horizontal back-link with Balance Free gas-charged shock, adjustable compression damping, adjustable rebound damping, stepless adjustable spring preload/4.5 in	Curb Weight	456.4 lb* (ABS), 452.0 lb* (non-ABS)
		Fuel Capacity	4.5 gal
		Wheelbase	57.1 in
		Special Features	4.3" Full-Color TFT Instrumentation, Smartphone Connectivity via RIDELOGY THE APP
		Color Choices	Metallic Flat Spark Black/Ebony
		Warranty	12 Month Limited Warranty