## **BRUTE FORCE® 450 4x4**









## **POWER**

Engine 4-stroke, single-cylinder, SOHC, liquid-cooled

Displacement 443cc

Bore x Stroke 89.0 x 71.2mm

Compression Ratio 9.1:1

Maximum 32.0

Horsepower

32.0 hp<sup>1</sup> @ 7,000 rpm

Maximum Torque 24.3 lb-ft @ 6,500 rpm

Fuel System FI with 38mm throttle body

**Ignition** Digital DC-CDI

Transmission Automatic Continuously Variable Transmission (CVT) with

centrifugal clutch (H,L,N,R)

Final Drive Selectable 2WD/4WD with dual-mode differential, shaft

## CAPABILITY

Front Suspension / Dual A-Wheel Travel

Dual A-arm, adjustable spring preload/7.6 in

Rear Suspension / Wheel Travel

Dual A-arm, adjustable spring preload/7.9 in

Front Tires AT 24 x 8-12

Rear Tires AT 24 x 10-12

Front Brakes Dual 202mm discs

Rear Brakes Single 202mm disc

Ground Clearance 9.3 in

Starting System Electric

Fuel Capacity 4.2 gal

Steering Conventional tie-rod

Turning Radius 10.2 ft

Towing Capacity 1,050 lb

Total Rack Capacity 225 lb

Rack Capacity, Front/ Rear

•

**Lighting** LED headlights, LED handlebar mounted light, Halogen

taillight

75/150 lb

## **DETAILS**

Frame Type Double-cradle, high-tensile tubular steel

Tread Width 35.8/34.2 in

Overall Length 80.1 in
Overall Width 43.7 in

Overall Height 46.7 in

Seat Height 34.6 in

Curb Weight 683.4 lb\* / 685.6 lb\* CA Model

Wheelbase 47.8 i

Instruments Speedometer, tachometer, gear position indicator, fuel

 ${\it gauge, clock, odometer, hour meter, trip\ meter, Differential}$ 

Lock/4WD indicator, etc.

Special Features KQR™ system-compatible front and rear cargo racks

Color Choices Grayish Blue, Firecracker Red

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.



\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit costa-rica.kawasaki-la.com for full product details.