

2026

BRUTE FORCE® 450 4x4 EPS

Kawasaki

Let the Good Times Roll®



- GRAYISH BLUE
- FIRECRACKER RED



| POWER                           |                                                                                      | Steering                  | Conventional tie-rod w/ Electric Power Steering (EPS)                                                                                        |
|---------------------------------|--------------------------------------------------------------------------------------|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Engine                          | 4-stroke, single-cylinder, SOHC, liquid-cooled                                       | Turning Radius            | 10.2 ft                                                                                                                                      |
| Displacement                    | 443cc                                                                                | Towing Capacity           | 1,050 lb                                                                                                                                     |
| Bore x Stroke                   | 89.0 x 71.2mm                                                                        | Total Rack Capacity       | 225 lb                                                                                                                                       |
| Compression Ratio               | 9.1:1                                                                                | Rack Capacity, Front/Rear | 75/150 lb                                                                                                                                    |
| Maximum Horsepower              | 32.0 hp <sup>1</sup> @ 7,000 rpm                                                     | Lighting                  | LED headlights, LED handlebar mounted light, Halogen taillight                                                                               |
| Maximum Torque                  | 24.6 lb-ft @ 6,500 rpm                                                               | DETAILS                   |                                                                                                                                              |
| Fuel System                     | FI with 38mm throttle body                                                           |                           |                                                                                                                                              |
| Ignition                        | Digital DC-CDI                                                                       | Frame Type                | Double-cradle, high-tensile tubular steel                                                                                                    |
| Transmission                    | Automatic Continuously Variable Transmission (CVT) with centrifugal clutch (H,L,N,R) | Tread Width               | 35.8/34.2 in                                                                                                                                 |
| Final Drive                     | Selectable 2WD/4WD with dual-mode front differential, shaft                          | Overall Length            | 80.1 in                                                                                                                                      |
| CAPABILITY                      |                                                                                      | Overall Width             | 43.3 in                                                                                                                                      |
| Front Suspension / Wheel Travel | Dual A-arm, adjustable spring preload/7.6 in                                         | Overall Height            | 46.7 in                                                                                                                                      |
| Rear Suspension / Wheel Travel  | Dual A-arm, adjustable spring preload/7.9 in                                         | Seat Height               | 34.6 in                                                                                                                                      |
| Front Tires                     | AT 24 x 8-12                                                                         | Estimated Dry Weight      | 672.5 lb** / 674.7 lb** CA Model                                                                                                             |
| Rear Tires                      | AT 24 x 10-12                                                                        | Curb Weight               | 712.2 lb* / 714.4 lb* CA Model                                                                                                               |
| Front Brakes                    | Dual 202mm discs                                                                     | Wheelbase                 | 47.8 in                                                                                                                                      |
| Rear Brakes                     | Single 202mm disc                                                                    | Instruments               | Speedometer, tachometer, gear position indicator, fuel gauge, clock, odometer, hour meter, trip meter, Differential Lock/4WD indicator, etc. |
| Ground Clearance                | 9.3 in                                                                               | Special Features          | KQR™ system-compatible front and rear cargo racks with carrier covers                                                                        |
| Starting System                 | Electric                                                                             | Color Choices             | Grayish Blue, Firecracker Red                                                                                                                |
| Fuel Capacity                   | 4.2 gal                                                                              | Warranty                  | 12 Month Limited Warranty                                                                                                                    |

Scan with camera to view videos, key features and more.

\*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

\*\*Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied)

<sup>1</sup>This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to [www.atvsafety.org](http://www.atvsafety.org). ©2026 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit [costa-rica.kawasaki-la.com](http://costa-rica.kawasaki-la.com) for full product details.