2026

BRUTE FORCE® 750 EPS

Kawasaki
Let the Good Times Roll®



GRAYISH BLUE



POWER

Engine	4-stroke, V-twin, SOHC, liquid-cooled
Displacement	749cc
Bore x Stroke	85.0 x 66.0mm
Compression Ratio	9.3:1
Maximum Horsepower	50.0 hp[1] @ 6,750 rpm
Maximum Torque	42.8 lb-ft @ 4,750 rpm
Fuel System	DFI® with two 34mm throttle bodies
Ignition	Digital DC-CDI
Transmission	Automatic Continuously Variable Transmission (CVT) with (H,L,N,R)
Final Drive	Selectable 2WD/4WD with variable control front differential lock, shaft

CAPABILITY

Front Suspension / Wheel Travel	Double wishbone, adjustable spring preload/6.9 in
Rear Suspension / Wheel Travel	Double wishbone, adjustable spring preload/7.4 in
Front Tires	AT 25 x 8-12
Rear Tires	AT 25 x 10-12
Front Brakes	Dual hydraulic 176mm discs with 2-piston calipers
Rear Brakes	Sealed, oil-bathed, multi-disc with independent park brake
Ground Clearance	9.0 in/9.7 in (max preload)
Starting System	Electric
Fuel Capacity	5.0 gal
Steering	Rack-and-pinion w/ Electric Power Steering (EPS)
Turning Radius	10.5 ft
Towing Capacity	1,250 lb
Total Rack Capacity	264.5 lb
Rack Capacity, Front/ Rear	88.0/176.0 lb
Lighting	All-LED lighting

DETAILS

Frame Type	Double-cradle, high-tensile tubular steel
Tread Width	37.0/35.6 in
Overall Length	86.0 in
Overall Width	46.1 in
Overall Height	47.6 in
Seat Height	35.2 in
Estimated Dry Weight	685.8 lb**
Curb Weight	732.1 lb*
Wheelbase	50.6 in
Instruments	Digital speedometer, 2WD/4WD drive indicator, fuel gauge, odometer, dual trip meters, dual hour meter, clock (12h/24h), battery voltage, Kawasaki service reminder, oil change reminder, high beam, neutral, reverse, and warning lights (engine, coolant temperature, CVT, oil, EPS, and battery voltage)
Special Features	Full-color TFT Instrumentation w/ Smartphone Connectivity via RIDEOLOGY THE APP POWERSPORTS, KQR™ system
Color Choices	Grayish Blue
Warranty	12 Month Limited Warranty

Scan with camera to view videos, key features and more.

*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).
[1]This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.
KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are intended for use only by persons 16 years of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, call the ATV Safety Institute at 1-800-887-2887, or go to www.atvsafety.org. © 2026 Kawasaki Motors Corp., U.S.A.
Specifications subject to change. Visit costa-rica.kawasaki-la.com for full product details.