2026

KLX[®]300









Single 250mm petal disc with a dual-piston

Single 240mm petal disc with single-piston

POWER

4-stroke, single-cylinder, DOHC, liquid-cooled **Engine**

Displacement 292cc

Bore x Stroke 78.0 x 61.2mm

Compression

Ratio

11.1:1

Maximum Horsepower

Maximum Torque

17.7 lb-ft @ 7,000 rpm

Fuel System

DFI® with 34mm Keihin throttle body

Ignition

Transmission

6-speed, return shift with wet multi-disc manual

clutch

Final Drive Chain

Frame Type 25.0 hp1 @ 8,000 rpm

Tubular, semi-double cradle 26.7° / 4.2 in

4.6 x 18

caliper

caliper

Rake/Trail

Rear Tire

Front Brakes

Rear Brakes

DETAILS

85.6 in

Overall Length Overall Width

32.3 in

Overall Height

46.7 in

Ground Clearance

10.8 in

Seat Height

35.2 in

Estimated Dry

Weight

282.2 lb**

Curb Weight

302.1 lb*

Fuel Capacity

2.0 gal

Wheelbase

56.7 in

Color Choices

Warranty

Lime Green, Bright White, Cypher Camo Beige/

12 Month Limited Warranty

PERFORMANCE

Front Suspension / Wheel Travel

43mm inverted telescopic fork with adjustable compression damping/10.0 in

Rear Suspension / Wheel Travel

Uni-Trak® gas charged shock with piggyback reservoir with adjustable compression, rebound damping and spring preload/9.1 in

Front Tire

3.0 x 21



