Z500 SE ABS









POWER

Engine 4-stroke, Parallel Twin, DOHC, liquid-cooled

Displacement 451cc

Bore x Stroke 70.0 x 58.6mm

Compression Ratio 11.3:1

Maximum 51.0 hp¹ @ 10,000 rpm

Horsepower

Maximum Torque 31.7 lb-ft @ 7,500 rpm

Fuel System DFI® with dual 32mm throttle bodies

Ignition TCBI with Electronic Advance

Transmission 6-speed

Final Drive Sealed chain

Electronic Rider Economical Riding Indicator, Anti-lock Brake System

Aids (AE

PERFORMANCE

Front Suspension / Wheel Travel

41mm hydraulic telescopic fork/4.7 in

Rear Suspension /

Horizontal back-link with adjustable spring

Wheel Travel preload/5.1 in

Front Tire 110/70-17

Rear Tire 150/60-17

Front Brakes Single 310mm semi-floating disc with 2-piston

calipers and ABS

Rear Brakes Single 220mm disc with single-piston caliper and ABS

DETAILS

Frame Type Trellis, high-tensile steel

Rake/Trail 24.5°/3.6 in

Overall Length 78.5 in

Overall Width 31.5 in

Overall Height 43.3 in

Ground Clearance 5.7 in

Seat Height 30.9 in

Estimated Dry Weight

Curb Weight

imated Dry 341.8 lb** 50-State Model; 339.6 lb** 49-State Model

Fuel Capacity 3.7 gal

Wheelbase 54.1 in

Special Features ERGO-FIT®, All-LED lighting, Full-color TFT

Instrumentation with Smartphone Connectivity via

372.6 lb* 50-State Model; 370.4 lb* 49-State Model

RIDEOLOGY THE APP, USB-C outlet

Color Choices Pearl Blizzard White/Ebony

Warranty 12 Month Limited Warranty

Scan with camera to view videos, key features and more.



*Curb weight includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied). When equipped, California evaporative emissions equipment adds approximately 2.2 lb.

**Dry weight does not include all necessary materials and fluids to operate correctly, full tank of fuel (more than 90 percent capacity) and tool kit (if supplied).

This vehicle's HP was measured according to ISO standard 4106. This ISO standard measures HP differently than the SAE standards by which the horsepower of many cars is measured, and as a result the referenced HP measurement may be higher than if it were measured by an SAE standard.

KAWASAKI CARES: Read Owner's Manual and all on-product warnings. Always wear a helmet, eye protection and proper apparel. Never ride under the influence of drugs or alcohol. Adhere to the maintenance schedule in your Owner's Manual. ©2025 Kawasaki Motors Corp., U.S.A.

Specifications subject to change. Visit costa-rica.kawasaki-la.com for full product details.